



BLUE STAR

Reach-in Chillers and Freezers



Easy storage meets accurate temperature control.

Blue Star's range of Reach-in Chillers and Freezers is specially designed for commercial kitchen needs. With upright cabinets that ensure convenient storage and retrieval, and an electronic panel that ensures accurate temperature control, this is the most reliable way of preserving food. Overall, these Chillers and Freezers have a robust design that helps in keeping food fresh for a longer period. Just what you'd expect from the Experts in cooling.

Features



Rounded corners



Removable gasket
for easy clean



Eco-friendly refrigerant



Adjustable tray slides



Odourless operation due to
continuous air circulation



Food grade stainless
steel unit



Tropicalised for high
ambient temperatures



Auto defrost



Uniform cooling by
forced air circulation



Self-closing doors

Technical Specifications - Reach-in Chillers

Description	Units	RCSD640A	RC2D640A	RCDD1390A	RC4D1390A
Gross Capacity	Ltr.	600	600	1300	1300
Temperature Range		2°C ~ 8°C	2° ~ 8°C	2° ~ 8°C	2° ~ 8°C
No. of Doors	Nos.	1	2	2	4
Shelves	Nos.	3	3	6	6
Internal Light	Nos.	1 LED (4.8 Watts)	1 LED (4.8 Watts)	2 LED (9.16 Watts)	2 LED (9.16 Watts)
Refrigerant	Type / Charge (Grams)	R134A / 250	R134A / 250	R134A / 300	R134A / 300
Power Supply	V/Hz	220-240V / 50 Hz	220-240V / 50Hz	220-240V / 50Hz	220-240V / 50Hz
Max. Input Power	W	322	322	524	524
Rated Current	A	3.1	4.5	4.5	5.2
Defrost		Automatic	Automatic	Automatic	Automatic
Thermostat Control		Digital	Digital	Digital	Digital
Overall Dimensions (W x D x H)	mm	700 x 820 x 2050	700 x 820 x 2050	1400 x 820 x 2050	1400 x 820 x 2050
Net Weight	kg	120	122	184	187

Technical Specifications - Reach-in Freezers

Description	Units	RFSD640A	RF2D640A	RFDD1390A	RF4D1390A
Gross Capacity	Ltr.	600	600	1300	1300
Temperature Range		-18°C ~ -22°C	-18° ~ -22°C	-18° ~ -22°C	-18° ~ -22°C
No. of Doors	Nos.	1	2	2	4
Shelves	Nos.	3	3	6	6
Internal Light	Nos.	1 LED (4.8 Watts)	1 LED (4.8 Watts)	2 LED (9.16 Watts)	2 LED (9.16 Watts)
Refrigerant	Type / Charge (Grams)	R404A / 290	R404A / 290	R404A / 440	R404A / 440
Power Supply	V/Hz	220-240V / 50 Hz	220-240V / 50Hz	220-240V / 50Hz	220-240V / 50Hz
Max. Input Power	W	750	750	880	880
Rated Current	A	7.1	7.1	8.5	8.5
Defrost		Automatic	Automatic	Automatic	Automatic
Thermostat Control		Digital	Digital	Digital	Digital
Overall Dimensions (W x D x H)	mm	700 x 820 x 2050	700 x 820 x 2050	1400 x 820 x 2050	1400 x 820 x 2050
Net Weight	kg	122	127	194	194

